



ENGINEERING DATA SHEET

RSa15i

60Hz

CCN: 47724923001
 Rev.: C
 ECN: 1491901
 Sheet: 1 of 1
 Date: Oct-23-2023

Model		RSa15i-A110	RSa15i-A125	RSa15i-A145	RSa15i-A200
GENERAL PERFORMANCE DATA					
Maximum Target Operating Pressure	⁽²⁾ barg (psig)	7.6 (110)	8.6 (125)	10.0 (145)	13.8 (200)
Rated Discharge Pressure	barg (psig)	6.9 (100)	7.9 (115)	9.3 (135)	13.1 (190)
Minimum Operating Pressure	barg (psig)	5.2 (75)	5.2 (75)	5.2 (75)	5.2 (75)
Maximum Operating Ambient Temperature	°C (°F)	40 (104)	40 (104)	40 (104)	40 (104)
Minimum Operating Ambient Temperature	°C (°F)	2 (36)	2 (36)	2 (36)	2 (36)
Maximum System Temperature Setting	°C (°F)	115.5 (240)	115.5 (240)	115.5 (240)	115.5 (240)
Nominal Power - Main Motor	kW (HP)	15.0 (20)	15.0 (20)	15.0 (20)	15.0 (20)
Main Motor Efficiency	%	91.0%	91.0%	91.0%	91.0%
Capacity FAD	⁽¹⁾ m ³ /min (CFM)	2.47 (87.1)	2.29 (81.0)	2.12 (75.0)	1.67 (58.8)
Package Input Power with Fan - Air Cooled	⁽⁴⁾ kW	17.61	17.56	17.87	18.26
Specific Power - Air Cooled	⁽⁴⁾⁽⁵⁾ kW/m ³ /min (kW/100CFM)	7.14 (20.22)	7.66 (21.68)	8.41 (23.82)	10.97 (31.06)
SOUND LEVEL					
Noise Level Standard Package - Air Cooled	⁽⁶⁾ Sound Pressure - dB(A)	70	70	70	70
Noise Level Standard Package - Air Cooled	Sound Power - dB(A)	85	85	85	85
COOLING DATA (@ Maximum Ambient Temperature & Maximum Discharge Pressure)					
Heat Removal (Oil Cooler)	kW (1000 Btu/hr)	14.6 (50)	14.8 (50)	15.3 (52)	15.9 (54)
Heat Removal (Oil and Aftercooler)	kW (1000 Btu/hr)	17.6 (60)	17.6 (60)	18.0 (61)	18.5 (63)
Permitted Additional Static Pressure	Pa (in H ₂ O)	40 (.16)	40 (.16)	40 (.16)	40 (.16)
Fan Air Flow	m ³ /min (CFM)	55 (1942)	55 (1942)	55 (1942)	55 (1942)
Fan Motor Nominal Power	⁽¹⁶⁾ kW	N/A	N/A	N/A	N/A
Cooling Air Temperature Rise @ 30°C	°C (°F)	15 (28)	15 (28)	16 (28)	16 (29)
Aftercooler CTD	⁽⁷⁾ °C (°F)	11 (19)	11 (19)	11 (19)	11 (20)
AIR END DATA					
Male Rotor Speed	RPM	3804	3565	3344	2784
Tip Speed Rotor	m/sec	20.12	18.85	17.68	14.72
Full Load Shaft Power	kW	16.0	16.0	16.3	16.6
COOLANT LUBRICATION DATA					
Total Coolant Capacity - Air Cooled	⁽¹²⁾ litres (US gal)	10 (2.5)	10 (2.5)	10 (2.5)	10 (2.5)
PIPING CONNECTIONS					
Air Discharge	⁽⁸⁾ Inches NPT	1.0" INCH (FEMALE)	1.0" INCH (FEMALE)	1.0" INCH (FEMALE)	1.0" INCH (FEMALE)
Package Automatic Condensate Drain	Inches NPT	.25 INCH (FEMALE)	.25 INCH (FEMALE)	.25 INCH (FEMALE)	.25 INCH (FEMALE)
Coolant Drain - Hose Size	Inches NPT	1/2 INCH (FEMALE)	1/2 INCH (FEMALE)	1/2 INCH (FEMALE)	1/2 INCH (FEMALE)
Diameter of Power Inlet	mm (Inches)	38 (1.5)	38 (1.5)	38 (1.5)	38 (1.5)
DIMENSIONS AND WEIGHT					
Length, Width, Height (Base Mounted)	mm (inches)	770, 870, 1160 (30.3, 34.3, 45.7)	770, 870, 1160 (30.3, 34.3, 45.7)	770, 870, 1160 (30.3, 34.3, 45.7)	770, 870, 1160 (30.3, 34.3, 45.7)
Net Weight - Air Cooled Base Mounted	kg (lb.)	443 (977)	443 (977)	443 (977)	443 (977)
GA Drawing Number - Air Cooled	Base Mounted	47763591	47763591	47763591	47763591
	Receiver Mounted	47749762	47749762	47749762	47749762
ELECTRICAL DATA					
Motor Protection	⁽¹³⁾	TEFC, IP55	TEFC, IP55	TEFC, IP55	TEFC, IP55
Full Load Package Current - Air Cooled	⁽⁹⁾ Amps @ 200V	63	62	64	65
	Amps @ 230V	55	54	55	57
	Amps @ 460V	28	27	28	29
	Amps @ 575V	22	22	22	23
Main Motor Locked Rotor Current	⁽¹⁴⁾ Amps @ 200V	434	434	434	434
	Amps @ 230V	503	503	503	503
	Amps @ 460V	252	252	252	252
	Amps @ 575V	220	220	220	220
Package Power Factor		0.90	0.90	0.90	0.90
Electrical Installation					
Recommended Supply Cable Size	⁽¹⁰⁾ mm ² /Cu (AWG) @ 200V	27 (3)	27 (3)	27 (3)	27 (3)
	mm ² /Cu (AWG) @ 230V	22 (4)	22 (4)	22 (4)	22 (4)
	mm ² /Cu (AWG) @ 460V	9 (8)	9 (8)	9 (8)	9 (8)
	mm ² /Cu (AWG) @ 575V	9 (8)	9 (8)	9 (8)	9 (8)
Maximum Recommended Fuse Rating	⁽¹⁰⁾⁽¹¹⁾ Amps @ 200V	90	90	90	90
	Amps @ 230V	80	80	80	80
	Amps @ 460V	40	40	40	40
	Amps @ 575V	35	35	35	35

Notes:

- FAD (Free Air Delivery) is full package performance including all losses. Tested per ISO 1217 : 2009 Annex C
- Maximum pressure at package discharge, value at which compressor will stop when unit operating at maximum target pressure
- IE3 efficiency motor
- Measured at rated capacity and rated pressure
- Specific power guaranteed in accordance with ISO 1217 : 2009 Annex C
- Measured in free field conditions per ISO 2151 using Parallelepiped Method; ducted inlet and outlet, with + 3 dB(A) tolerance
- CTD based on 100°F/38°C inlet air at 40% Relative Humidity (For alternate conditions contact Ingersoll Rand)
- BSP or NPT, depending on regional standard
- Maximum current includes 10% additional current due to fouled filters and elements
- 90°C copper cables. Always apply local electrical codes for sizing cables and system protection
- Time delay fuse recommended. Apply local electrical codes for fuse sizing
- Coolant volumes listed are approximate. See operator manual for coolant fill procedure
- 60Hz (±0.5%) motor voltage tolerance: (200)±10%; (220)±10%; (230)±10%; (380)-6/+10%; (440) ±10%; (460) ±10%; (575) -6/+10%
- Star-Delta starting current inrush is about 33% of direct starting current
- During the Star-Delta open-starting transition, the in-rush current value could instantaneously peak from 1.8 to 2.8 times the noted Locked-Rotor-Amperage (LRA) values
- Package cooling fan mounted to main drive motor shaft extension.

Product Improvement is a continuing goal at Ingersoll Rand. Design and specifications are subject to change without notice or obligation.