

S Class





POWERED by
HONDA

- Full Power Switch
- 2 Large fuel tank with fuel gauge
- 3 1 1/4" frame protects the generator and can be used for lifting
- Powered by Honda OHV engine (\$2800 powered by Subaru)
- **5** Easy access fuel valve
- 6 Premium alternator provides less than 6% harmonic distortion
- 7 Broad selection of receptacles including GFCI and twist lock
- 8 Hydraulic/magnetic circuit breaker provides overload protection
- 9 Optional wheel kit available (included with \$14000)
- 10" Flat-Free solid foam wheels (13" pneumatic on the S14000)







S Class

S2800



Manual Start

Model No.	S2800	
Rated Watts	2400 Watts	
Surge Watts	2800 Watts	
Engine	Subaru	
Engine Displacement	169cc	
Low Oil Shutdown	Yes	
Spark Arrestor/Muffler	Yes	
Fuel Tank Capacity	.95 Gallons	
Fuel Gauge	No	
Run Time @50% Load	2.6 Hours	
Assembled Dimensions	21.8"L x 14.4"W x 16.6"H	
Dry Weight	73 lbs.	
(4) 5 00D 0E0LD 1 100V		

(1) 5-20R GFCI Duplex 120V

S4500



Manual Start

	Model No.	\$4500
	Rated Watts	4200 Watts
	Surge Watts	4500 Watts
	Engine	Honda
	Engine Displacement	270cc
	Low Oil Shutdown	Yes
	Spark Arrestor/Muffler	Yes
	Fuel Tank Capacity	7.0 Gallons
	Fuel Gauge	Yes
	Run Time @50% Load	15.2 Hours
	Assembled Dimensions	29.1"L x 22.3"W x 25.6"H
	Dry Weight	166 lbs.
ш	<u>'</u>	<u> </u>

(2) 5-20R GFCI (1) L5-30R Duplex 120V

(1) L14-20R 120/240V

S6000

(2)



Manual Start

Model No.	S6000
Rated Watts	5300 Watts
Surge Watts	6000 Watts
Engine	Honda
Engine Displacement	389cc
Low Oil Shutdown	Yes
Spark Arrestor/Muffler	Yes
Fuel Tank Capacity	8.0 Gallons
Fuel Gauge	Yes
Run Time @50% Load	13.7 Hours
Assembled Dimensions	31.4"L x 22.3"W x 26.3"H
Dry Weight	190 lbs.

(1) L5-30R 120V (2) 5-20R GFCI Duplex 120V

(1) L14-30R 120/240V

S7200



(2)

Manual/Electric Start

Model No.	\$7200
Rated Watts	6100 Watts
Surge Watts	7200 Watts
Engine	Honda
Engine Displacement	389cc
Low Oil Shutdown	Yes
Spark Arrestor/Muffler	Yes
Fuel Tank Capacity	8.0 Gallons
Fuel Gauge	Yes
Run Time @50% Load	12.9 Hours
Assembled Dimensions	31.4"Lx22.3"Wx26.3"H
Dry Weight	201 lbs.
	·

(2) 5-20RGFCI Duplex 120V (1) L5-30R 120V

(1) L14-30R 120/240V

S14000



(2) (3)

Electric Start

Model No.	S14000
Rated Watts	11700 Watts
Surge Watts	14000 Watts
Engine	Honda
Engine Displacement	688cc
Low Oil Shutdown	Yes
Spark Arrestor/Muffler	Yes
Fuel Tank Capacity	8.0 Gallons
Fuel Gauge	Yes
Run Time @50% Load	6.5 Hours
Assembled Dimensions (L x W x H)	38.9" x 22.4" x 32"
Dry Weight	316 lbs.

(2) 5-20R GFCI Duplex 120V

(1) 14-50R 120/240V

(1) L14-30R 120/240V

(888) 977-2622 www.pramac.com Manufactured in Kearney, NE Pramac America, LLC, Marietta, GA 30062. © 2012 Pramac America, LLC. All Rights Reserved. Product style and configuration may vary. PRAS0113

