

## SPECIFICATIONS

Model Number	926081	926091
<b>Description</b>	Hydro Pro 36 EFI	Hydro Pro 28 EFI RapidTrak
<b>Engine</b>	Ariens AX420 EFI	
Gross Torque* – N•m (lb-ft)	28.6 (21.0)	
Displacement – cm <sup>3</sup> (in <sup>3</sup> )	420.0 (25.6)	
Maximum RPM – No load	3600 ± 50	
Electric Start	120V	
Fuel Tank Capacity – liter (qt)	2.8 (3.0)	
<b>Headlight</b>	LED	
<b>Chute</b>		
Chute Rotation Angle	200°	
Rotation Control	Quick Turn	Electric
Deflector Control	In-Dash Lever	Electric
<b>Auger</b>		
Snow Clearing Width – cm (in)	91.4 (36.0)	71.1 (28.0)
Gearcase	Cast Iron	
Auger Diameter – cm (in)	40.6 (16.0)	
<b>Impeller</b>		
Impeller Diameter – cm (in)	35.6 (14.0)	
Impeller Speed (RPM)	1059	
Impeller Tip Speed – m/sec (ft/sec)	19.7 (64.6)	
<b>Drive</b>		
Auger	Dual HA Belt	
Traction	Hydrostatic	
Speeds	Infinitely Variable	
Axle Control	Auto-Turn™	
<b>Tires</b>		
Size – in	16 x 6.5-8	N/A
Rubber Track Size – cm (in)	N/A	14.0 (5.5) Track
Pressure	See tire sidewall.	N/A
<b>Size and Weight</b>		
Length – cm (in)	153.2 (60.3)	153.9 (60.6)
Height – cm (in)	118.4 (46.6)	116.6 (45.9)
Width – cm (in)	97.0 (38.2)	76.7 (30.2)
Weight – kg (lb)	145.2 (320.0)	153.8 (339.0)

\*Engine output stated in gross torque per SAE J1940 as rated by engine manufacturer.