

## 30 Gallon - Two Stage Cast Iron Industrial Compressor with Generator & Welder

### FEATURES & BENEFITS

- **HONDA GX390 OHV gas engine *with electric start***
  - OHV design for increased efficiency and optimal power transfer
  - EPA & CARB approved
  - Automatic low oil shutdown
  - Automatic idle control
- Industrial two stage compressor pump provides 13.6 SCFM @ 100 PSI
- Automotive style poly-v drive belt system – requires minimal belt adjustments
- 175 PSI maximum operating pressure provides enough power to operate more than one air tool or device at one time
- 5500 watt generator with 120V and 240V GFCI protected receptacles
- 50-200 Amp DC output welder
- 30 gallon truck mount style ASME\* tank
- Isolated platform design to absorb engine & pump vibration
- Perfect for service truck and field service applications



### MODEL SPECIFICATIONS

Tank Size:	30 Gallon ASME*
Maximum Pressure:	175 PSI
SCFM @ 100 PSI:	13.6
SCFM @ 175 PSI:	13.3
Engine CC:	389
Engine Type:	HONDA OHV
Generator:	5500 Continuous Watts 60 Hertz CE approval
Welder:	50-200 Amp DC CE approval
Limited Warranty:	2 Year Pump 1 Year All Other Parts
Model Number:	GR3200
UPC Number:	0 45564 63763 7

Dimensions: 58" x 32" x 53" • Weight: 542 lbs. • Truckload Qty: (53' trailer) • Pallets Crated: 28

\*ASME - American Society of Mechanical Engineers

Product style and configuration may vary.



### INTEGRATED WELDER

- 50-200 Amp DC output welder designed for Shielded Metal Arc Welding (stick welding)
- Allows you to weld DC stick electrodes 3/32" to 7/32" in size
- Capable of welding steel, stainless steel, and cast iron alloys between 1/16" minimum and 1/2" maximum thickness
- Rated output: 50-150A @ 100% duty cycle, 180A @ 60%, 200A @ 50%



### INTEGRATED GENERATOR

- 5500 Continuous Watt / 6050 Surge Watt
- Equipped with
  - (2) Duplex 120V 20 Amp receptacles
  - (1) 120/240V 30 Amp twist lock receptacle
  - GFCI protected panel
  - GFCI circuit breaker lever can be switched off to stop all power when needed

### ASME TANK

- 30 Gallon horizontal truck mount style tank
- Meets the requirements of the ASME Boiler & Pressure Vessel Code
- CRN (Canadian Registration Number) approved & assigned
- In-platform manifold with regulator, liquid filled tank & working pressure gauges, (2) 1/4" I/M series quick couplers, & pressure relief valve
- Isolated platform design to absorb engine & pump vibration
- Channel foot design with forklift access



Patent Pending

### COMPRESSOR PUMP

- Industrial two stage compressor pump provides 13.6 SCFM @ 100 PSI and 13.3 SCFM @ 175 PSI
- Cast iron construction for durability, dependability, and smooth operation
- Free-floating stainless steel valves
- Four rings per piston for improved volumetric efficiencies & oil control
- Large easy view oil level sight glass
- One-piece crankshaft