

## 6-INCH KINETIC CYCLONIC ELECTRIC START DRUM CHIPPER SHREDDER

### ITEM NUMBER

OPC566E

### UPC

827518006757

26



### DESCRIPTION

The OPC566E is a 6-inch kinetic cyclonic chipper powered by an electric start, direct drive KOHLER® Command PRO® CH440 14HP 429cc engine with 22.7ft/lb gross torque to demolish trees up to 6.25 inches in diameter. Equipped with double edge reversible 12-inch cutting blades that auto-adjust to pulverize trees and brush, dual tool-free swing-open chutes that quickly open for easy drum access, D.O.T. approved tires and a 48-inch extended axle for uneven ground and towing stability with front articulated ground wheels for easy equipment moving, a 2-inch hitch receiver and tow bar, and a rotational expulsion chute pickup truck height for bed loading.

### SPECIFICATION

<b>ENGINE</b>	KOHLER® Command PRO® CH440 14HP 429cc
<b>GEARBOX</b>	Direct drive 22.7ft/lb (30.7Nm) gross torque
<b>REAR WHEELS &amp; TIRES</b>	D.O.T. approved 4.80-8 Ø15" (Ø41.9cm) OD x 4.25" (10.8cm) on 9" (22.9cm) rims
<b>FRONT WHEELS &amp; TIRES</b>	Off-road 4.10-4 Ø10" (Ø25.4cm) OD on Ø5" (Ø12.7cm) rims
<b>WHEELBASE</b>	48" (121.9cm)
<b>CHIPPING CAPACITY</b>	Ø6.25" (Ø15.9cm)
<b>CUTTERS</b>	12" (30.5cm) double edge reversible chipper blades
<b>CHIPPER SHREDDER</b>	Auto-adjusting from Ø1/8" (Ø0.32cm) up to Ø6.25" (Ø15.9cm) trees and brush
<b>EXPULSION CHUTE</b>	59" (149.9cm) truck bed height with 180° adjustable spout
<b>COUPLER</b>	2" (5.08cm)
<b>DIMENSIONS</b>	102" (L) x 47" (W) x 59" (H) 259.1cm (L) x 119.4cm (W) x 149.9cm (H)
<b>WEIGHT</b>	594lb (269.4kg)
<b>SHIPPING DIMENSIONS</b>	45" (L) x 31" (W) x 48" (H) 114.3cm (L) x 78.7cm (W) x 121.9cm (H)
<b>SHIPPING WEIGHT</b>	726lb (329.3kg)
<b>WARRANTY</b>	3-year KOHLER® engine 1-year DK2 chassis



### FEATURES

- Powered by a KOHLER® Command PRO® CH440 14HP 429cc engine **1**
- Dual-belt drive drum transmission with 12" (30.5cm) double edge reversible cutting blades **2**
- Auto adjust cutters for trees and brush up to 6.25" (15.9cm) in diameter
- Extended 48" (121.9cm) axle with D.O.T. approved 4.80-8 Ø15" (Ø41.9cm) OD rear tires on Ø9" (Ø22.9cm) rims and off-road 4.10-4 Ø10" (Ø25.4cm) OD front tires on Ø5" (Ø12.7cm) rims **3**
- Includes safety glasses, ear protection, work gloves and assembly tools
- Electric start (battery included) **4**
- CE safety approved shutoff
- Dual tool free swing open chutes
- Tool-free 180° rotational spout on 59" (149.9cm) truck bed height expulsion chute
- Extra-large feed chute with integrated equipment moving handles
- Includes 3-year KOHLER® engine and 1-year DK2 chassis warranty
- **NOT HIGHWAY TOWABLE AND MAX SPEED 25MPH (40KM/H)**

