


## 7.5hp -10hp Standard Drive Complete Rotary Air System





Our Rotary screws are the most energy efficient with our soft start by limiting the voltage upon start up

- Reduces energy demand up to 33%
- 70,000 + running hours



- Schneider Internal Electrical circuit
- breakers UL/CSA listed
- Mann Filters
  - VMC inlet valve and load Solenoid
- Schneider y Delta magnetic contactors UL/CSA listed
- VMC inlet valve and load solenoid
- \*10 Year warranty on airend- 5 year on the cabinet and components



PLC Controller monitors maintenance, temp, oil level, filtration, hours, plus remote start/stop, timed start/stop automatic restart



Patented swing arm mount for quick and easy maintenance, simply take out the pin and swing the dryer to the side accessing the door panel.

Making the unit more compact taking up less space!

| Making the unit more cor | npact           |                 |                                |                 |
|--------------------------|-----------------|-----------------|--------------------------------|-----------------|
| taking up less space!    | •               |                 |                                |                 |
|                          | ERSK070001      | ERSK070003      | ESRK100001                     | ERSK100003      |
| Running HP               | 7.5             | 7.5             | 10                             | 10              |
| CFM 100PSI               | 29              | 29              | 45                             | 45              |
| MAX PSI                  | 145             | 145             | 145                            | 145             |
| <b>Drive Type</b>        | Belt            | Belt            | Belt                           | Belt            |
| Tank Size                | 120 Gal         | 120 Gal         | 120 Gal                        | 120 Gal         |
| Airend Model             | Rotocomp-EVO02  | Rotocomp-EVO02  | Rotocomp-EVO02                 | Rotocomp-       |
|                          |                 |                 |                                | EVO02           |
| Dryer CFM                | 30 CFM          | 30 CFM          | 58 CFM                         | 58CFM           |
| Outlet size              | 3/4"            | 3/4"            | 3/4"                           | 3/4"            |
| <b>Motor Phase</b>       | Single 230V     | Three           | Single 230V                    | Three           |
| Dimensions               | 71" x 27" x 70" | 71" x 27" x 70" | 71" x 27" x 70"                | 71" x 27" x 70" |
| Weight                   | 1236            | 1236            | 1288                           | 1288            |
|                          | USA, Germany,   | USA, Germany,   | USA, Germany,                  | USA,            |
| Product Source           | Italy           |                 | ty is only valid with annual p |                 |

1000 Cass Drive Englewood, OH 45315 Toll Free: 866-294-4153 Fax: 937-540-1157



