

Cast Iron Shallow Well Jet Pumps

With Built-in Pressure Switch

Rugged Pump Housing

Durable cast iron construction

Superior Performance

At depths to water of 25' or less

Heavy-Duty Dual-Voltage Motor

3/4 HP preset at 230V

1/2 HP preset at 115V;

Self-Priming After Pump Housing Is Initially Filled

Check valve or foot valve required, sold separately



3/4 HP 14.7 GPM
FP4122

1/2 HP 8.8 GPM
FP4112

PERFORMANCE (GPM)							MAX PRESSURE SHUTOFF	VOLTAGE	PRESSURE SWITCH	
DEPTH TO WATER	0'	5'	10'	15'	20'	25'			ON	OFF
FP4122	14.7	14.4	12.8	11.8	9.4	7.3	70 PSI	115/230	30	50
FP4112	8.8	8.5	7.8	6.8	5.6	4.6	69 PSI	115/230	30	50

• All performance shown in gallons per minute at 40 PSI discharge pressure

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FP4122	1 YEAR	022315100619	21.5" x 13.44" x 10.33"	24	43.3 LBS.
FP4112	1 YEAR	022315100602	21.5" x 13.44" x 10.33"	24	41 LBS.

Includes:

Factory-installed 30/50 preset pressure switch, detailed owner's manual

