

**Submittal Data:36RCLX
Inverter Driven Heat Pump**

36,000 BTU Ceiling Cassette

Job Name: _____

Date: _____

Location: _____

Approval: _____

Engineer: _____

Construction: _____

Submitted to: _____

Unit #: _____

Submitted by: _____

Drawing #: _____

Reference: _____

General Features

- Refrigerant Type R410A.
- Wired remote controllers
- 4-way air distribution
- Pump Down Operation
- Group control
- 2- Years Parts, 6-Years Compressor Warranty (See Warranty Statement for details)
- 24 hr. Timer



Model Information

Condenser..... AOU36RLX
Cassette..... AUU36RCLX

Electrical
Available Voltage Range..... 208/230V AC 1ph-60Hz
Max Fuse Size..... 30 A
Max Starting Current..... 10 A

Input Power

Cooling..... 4.2 kW
Heating..... 3.70 kW

Running Current

Cooling..... 18.8 A
Heating..... 18.8 A

Capacity

Nominal Cooling..... 34,100 Btu/h
Rated / Max Cooling..... 34,100 / 36,000 Btu/h
Nominal Heating..... 36,000 Btu/h
Rated / Max Heating..... 36,000 / 42,700 Btu/h

Compressor DC Twin Rotary (Inverter)

Motor Output..... 1,300 W
Refrigerant..... R410a
Charge..... 4 lbs. 13-19/32 oz.
Oil..... POE

Fan Motor

(Condenser) Type: DC..... Propeller x1
(Condenser) Motor Output..... 100 W
(Cassette) Type: DC..... Turbo x2
(Cassette) Motor Output..... 100 W
Thermal Protection
Condenser..... 302 ± 9°F
Cassette..... 302 ± 9°F

Heat Exchanger

Condenser
(H x W x D) in. (mm)..... 31-13/32 x 35-7/16 x 1-7/16 (798x900x36.38)
Fin Pitch..... 20 FPI
Rows x Stages..... 2 x 38
Pipe Type (Material)..... Copper
Fin Type (Material)..... Aluminum

Operation Temperature Range

Cooling..... 0°F - 115°F (-18°C - 46°C)
Heating..... 14°F - 75°F (-10°C - 24°C)

Efficiency

SEER..... 14.0
HSPF (heating)..... 8.5 Btu/hW

Enclosure

(Condenser) Material..... Steel
(Condenser) Color..... Beige (approximate color or Munsell 10 YR 7.5/1.0)
(Cassette) Material..... Polystyrene
(Cassette) Color..... White (5Y9/0.5NN)

Sound Pressure Level

Condenser..... 55 dB (A)
Cassette..... 48 dB (A)

Dimensions

H x W x D
Condenser in. (mm)..... 32-11/16 x 35-7/16 x 13 (830x900x330)
Cassette in. (mm)..... 11-21/32 x 32-11/16 x 32-11/16 (296x830x830)

Connection Pipe

Liquid..... 3/8"
Gas..... 5/8"
Method (Liquid/Gas)..... Brazing
Pre-charge..... 49 ft. (15 m)
Minimum Length..... 16 ft. (5 m)
Max Length..... 164 ft. (50m)
Max Height Difference..... 66 ft. (20m)

Weight

Condenser..... 141 lbs. (64 kg)
Cassette..... 82 lbs. (37 kg)

Accessories

Wired Remote Controller..... UTY-RNBYU

Safety Devices

(Condenser) Current Fuse on Main PCB..... 3.15A 250V & 5A 250V
Compressor Protection (Thermal protector)..... off: 257°F on: 176°F
High Pressure Protection..... off: 609±15psi on: 464±22psi
(Evaporator) Current Fuse on Main PCB..... 3.15A 250V

Note: Specifications are based on the following conditions:

Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB.
Heating: Indoor temperature of 70°F (21.1°C) DB/59°F (15°C) WB, and outdoor temperature of 47°F (8.33°C) DB/43°F (6.11°C) WB.
Pipe length: 24ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit)



Dimensions:36RCLX

[Unit: in. (mm)]

