

SAFETY DATA SHEET-Quicksilver Semi Synthetic 25W40 Engine Oil

1. IDENTIFICATION

1.1. PRODUCT IDENTIFIER USED ON LABEL:

1.1.1. QUICKSILVER SEMI SYNTHETIC 25W40 ENGINE OIL

1.2. OTHER MEANS OF IDENTIFICATION: 168-6078Q

1.2.1. 25W40 ENGINE OIL

1.2.2. 92-858055Q01; 92-8M0078623; 92-858052Q01; 92-8M0078624; 92-8M0061368; 92-8M0078622;
92-8M0061369; 92-8M0090502, 92-0053664, 92-8580119Q01, 92-8M0078635, 92-8M0078636

1.3. RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE;

1.3.1. PETROLEUM LUBRICATING OIL

1.3.2. NO OTHER USES RECOMMENDED

1.4. NAME, ADDRESS, AND TELEPHONE NUMBER OF THE CHEMICAL MANUFACTURER, IMPORTER, OR OTHER RESPONSIBLE PARTY:

1.4.1.

Mercury Marine

P.O. Box 1939
Fond du Lac, WI 54935
United States of America

Product Information

General Information: +1 (920) 929-5000

1.5. EMERGENCY PHONE NUMBER:

1.5.1.

Emergency Response

North America: CHEMTREC (800) 424-9300 after 5:00pm CST Or +17035273887

2. HAZARD(S) IDENTIFICATION

SAFETY DATA SHEET-Quicksilver Semi Synthetic 25W40 Engine Oil



- 2.1.
2.2. **WARNING:** MAY CAUSE EYE IRRITATION. HARMFUL SWALLOWED
2.3. Inhalation: No hazard in normal consumer use.
2.4. Eye Contact: May cause slight irritation.
2.5. Skin Contact: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis)
2.6. Ingestion: Small amounts (a tablespoon) normally are not likely to cause injury; swallowing amounts larger than that may cause injury.
2.7. Other: Not determined.

3. Composition/ information on ingredients

3.1.

COMPONENTS	CAS Number	%	ACGIH TWA	OSHA PEL	OSHA STEL	Skin
Zinc alkyl dithiophosphate	68649-42-3	1-3	--	--	--	NO
Proprietary materials	Mixture	Balance	5 mg/m ³ (oil mist)	5 mg/m ³ (oil mist)	5 mg/m ³ (oil mist)	No

4. FIRST AID MEASURES

4.1.

Inhalation:	No specific treatment is necessary since this material is not likely to be hazardous by inhalation. If exposed to excessive levels of dusts or fumes, remove to fresh air and get medical attention if cough or other symptoms develop.
Eye:	Immediately flush eyes with plenty of water. Get medical attention if irritation persists.
Skin Contact:	Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention.
Ingestion:	Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention (vomiting increases risk of lung aspiration). Do not give anything by mouth to an unconscious person.
Other	Not determined.

5. FIRE FIGHTING MEASURES

SAFETY DATA SHEET-Quicksilver Semi Synthetic 25W40 Engine Oil

5.1. Flash point:

5.1.1. >200°C (Cleveland open cup tester.)

5.2. Flammable limits:

5.2.1. Not determined.

5.3. Extinguishing media:

5.3.1. Use foam, dry chemical, or water spray to extinguish fire.

5.4. Special firefighting procedures:

5.4.1. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to cool fire exposed surfaces and to protect personnel.

5.5. Unusual fire & explosion hazards:

5.5.1. Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. Heavy flammable vapors may settle along ground level and low spots to create an invisible fire hazard. The vapors may extend to sources of ignition and flash back.

5.6. Byproducts of combustion:

5.6.1. Fumes, smoke, oxides of carbon, sulfur, phosphorus, zinc and nitrogen.

5.7. Auto ignition temperature:

5.7.1. Not determined

5.8. Explosion data:

5.8.1. Not determined. Care should always be exercised in dust/mist areas.

5.9. Other:

5.9.1. Not determined.

6. ACCIDENTAL RELEASE MEASURES

6.1. Spill control procedures (land):

6.1.1. Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (Section 15) notify the National Response Center. Prevent liquid from entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust. Recover by explosion proof pump, hand pump, or suitable absorbent, into appropriate containers. Dispose of in accordance to local ordinances.

6.2. Spill control procedures (water):

6.2.1. Eliminate sources of ignition. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear. Remove from surface by skimming or with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants

SAFETY DATA SHEET-Quicksilver Semi Synthetic 25W40 Engine Oil

may be used in non-confined waters. Recover adsorbed material into suitable containers and dispose of in accord with local disposal codes.

6.3. Waste disposal method:

6.3.1. Most oil based products are incinerated, land-filled or reclaimed. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.

6.4. Other:

6.4.1. CAUTION- If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.

7. HANDLING AND STORAGE

7.1. Handling procedures:

7.1.1. Keep containers closed when not in use. Do not transfer to unmarked containers. Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106--Flammable and Combustible Liquids. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

7.2. Storage procedures:

7.2.1. Store containers such that they are protected from weather elements (rain, snow, direct sunlight). Containers may absorb water through container closures if stored improperly. Store containers away from heat, sparks, open flame, or oxidizing materials

7.3. Additional information:

7.3.1. No additional information.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1. Personal protection:

8.1.1. Applicable mainly to persons in repeated contact situations such as packaging of product, service/maintenance, and cleanup/spill control personnel.

8.2. Respiratory protection:

8.2.1. None required if airborne concentrations are maintained below threshold limits listed on page one. Otherwise a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must

SAFETY DATA SHEET-Quicksilver Semi Synthetic 25W40 Engine Oil

be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-mask form dust/mist air purifying respirator.

8.3. Eye protection:

8.3.1. Eye protection is recommended. If material is handled such that it could be splashed into the eyes - or there is any concern, wear safety glasses with side shields or vented/splash proof goggles (ANSI Z87.1 or approved equivalent).

8.4. Hand protection:

8.4.1. Impervious gloves such as neoprene or nitrile rubber to avoid skin sensitization and absorption.

8.5. Other protection:

8.5.1. Use of an apron and over boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization and absorption. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other materials which cannot be decontaminated.

8.6. Local control measures:

8.6.1. Use adequate ventilation when working with material in an enclosed area. Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in areas where this material is used and stored.

8.7. Other:

8.7.1. Consumption of food and drink should be avoided in work areas where product is present. Always wash hands and face with soap and water before eating, drinking or smoking.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1.

9.1.1. Vapor Pressure:	Negligible at ambient conditions.
9.1.2. API Gravity:	28.5
9.1.3. Specific Gravity:	0.8840 at 15.6°C (60.0°F)
9.1.4. Solubility:	Negligible in water, soluble in most petroleum solvents.
9.1.5. Percent Volatile:	Negligible
9.1.6. Evaporation Rate (n-Butyl Acetate=1)	Negligible
9.1.7. Vapor Density (Air=1):	Greater than air.

SAFETY DATA SHEET-Quicksilver Semi Synthetic 25W40 Engine Oil

9.1.8. Odor:	Mild, bland hydrocarbon odor.
9.1.9. Color:	Amber
9.1.10. Physical State:	Viscous Fluid
9.1.11. Viscosity:	Approximately 15.95 cSt @ 100°C (212°F)
9.1.12. Boiling Point:	Not determined
9.1.13. Pour Point:	Not determined
9.1.14. Other:	Not determined

10. STABILITY AND REACTIVITY

10.1. **Stability:**

10.1.1. Stable

10.2. **Incompatibility:**

10.2.1. Avoid contact with acids and oxidizing materials such as liquid chlorine or concentrated oxygen.

10.3. **Hazardous Polymerization:**

10.3.1. Will not occur.

10.4. **Hazardous Decomposition Products:**

10.4.1. Smoke, carbon monoxide and dioxide, and other aldehydes of incomplete combustion. Oxides of carbon, carbon, sulfur, zinc, phosphorus and nitrogen.

10.5. **Conditions to Avoid:**

10.5.1. Avoid high temperatures and product contamination.

10.6. **Other:**

10.6.1. Not determined.

11. TOXICOLOGY INFORMATION

11.1. **Oral toxicity:**

11.1.1. Not determined

11.2. **Dermal toxicity:**

11.2.1. Not determined.

11.3. **Inhalation toxicity:**

11.3.1. On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptotic as a result of repeated small aspirations. Shortness of breath and cough are the most common symptoms. Based on data from similar materials.

11.4. **Dermal sensitization:**

SAFETY DATA SHEET-Quicksilver Semi Synthetic 25W40 Engine Oil

11.4.1. Prolonged or repeated contact may make skin more sensitive to other skin sensitizers. Based on data from similar materials.

11.5. Chronic toxicity:

11.5.1. Not determined.

11.6. Carcinogenicity:

11.6.1. Not determined.

11.7. Reproductive toxicity:

11.7.1. Not determined.

11.8. Other:

11.8.1. These products contain petroleum base oils (additive carriers) which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydro treating. None of the oils require a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B).

12. ECOLOGICAL INFORMATION

12.1. Environmental toxicity:

12.1.1. This material has not been evaluated for its environmental impact. This material may be toxic to aquatic organisms and should be kept out of sewage and drainage systems and all bodies of water. Based on data from similar materials.

12.2. Environmental Fate

12.2.1. This product has not been evaluated for its environmental fate.

12.3. Other:

12.3.1. Not determined.

13. DISPOSAL CONSIDERATIONS

13.1. Waste Disposal:

13.1.1. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. This product unadulterated by other materials may be classified as a non-regulated waste in some areas - but still needs to be disposed of at approved facilities. Waste management should be in full compliance with federal, state, and local laws.

13.2. Disposal consideration:

13.2.1. Most used oil and grease is reclaimed or incinerated (if unadulterated). Place used, contaminated, or excess material into disposable containers and dispose of in a manner consistent with local and state regulations. Contact local environmental or health authorities for approved disposal of this material.

13.3. Other:

13.3.1. If material is contaminated with a regulated material, the whole of the material becomes a regulated waste. Try to segregate from regulated material waste streams.

14. TRANSPORTATION INFORMATION

The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.

14.1. LAND (DOT):

14.1.1. Not regulated for Land Transport.

14.2. LAND (TDG):

14.2.1. Not regulated for Land Transport.

14.3. SEA (IMDG):

14.3.1. Not regulated for Sea Transport according to IMDG-Code.

14.4. AIR (IATA):

14.4.1. Not regulated for Air Transport.

15. REGULATORY INFORMATION

15.1. TSCA Inventory

15.1.1. All components of this material are listed in the U.S. TSCA Inventory.

15.2. Other TSCA:

15.2.1. Not applicable.

15.3. Clean Water Act (CWA)

15.3.1. This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

15.4. SARA Title III:

15.4.1. Section 302/304 extremely hazardous substances:

15.4.1.1. None.

15.4.2. Section 311, 312 hazard categories:

15.4.2.1. Acute (immediate health effects): YES

15.4.2.2. Chronic (delayed health effects): NO

15.4.2.3. Fire (hazard): NO

15.4.2.4. Reactivity (hazard): No

15.4.2.5. Pressure (sudden release hazard): NO

15.4.3. Section 313 toxic chemicals:

15.4.3.1. 1-3% zinc compounds

15.4.3.2. 0-0.5% zinc.

15.5. CERCLA

15.5.1. For stationary/moving sources-reportable quantity (due to): Not regulated/not applicable.

15.6. Other:

15.6.1. Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.

16. OTHER INFORMATION

16.1.

HAZARD RANKINGS		
	NFPA 704	NPCA-HMIS
HEALTH HAZARD	0	0
FIRE HAZARD	1	1
INSTABILITY/REACTIVITY	0	0
Specific Hazard	None	N/A
Protection Index	N/A	B

16.2. **Precautionary labels:**

16.2.1. MAY CAUSE EYE IRRITATION

16.2.2. HARMFUL IF SWALLOWED

16.3. **Date of preparation:** November 14, 2013

16.4. This product may be formulated with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Mercury Marine must rely on information provided by those materials manufacturers or distributors.

16.5. **MANUFACTURERS DISCLAIMER:**

16.5.1. *The data presented herein is based upon tests and information, which we believe to be reliable. However, users should make their own investigations to determine the suitability of the information for their particular purpose*