


Configuration	High Cart		Low Rider
Name	1140I	1140IA	1140
Model #	2419294	2419291	805-012
<b>Specifications</b>			
Gallons per minute	1.20 (4.54 LPM)	1.20 (4.54 LPM)	1.20 (4.54 LPM)
Maximum tip sizes	0.034"	0.034"	0.034"
Maximum pressure	3300 PSI (22.8 MPa)	3300 PSI (22.8 MPa)	3300 PSI (22.8 MPa)
Weight	103.3 lbs.	103.5 lbs.	100 lbs.
Maximum hose length	300'	300'	300'
Power	2.6 HP Brushless DC Motor, 100~120V AC, 50/60Hz, 15A	2.6 HP Brushless DC Motor, 100~120V AC, 50/60Hz, 15A	2.6 HP Brushless DC Motor, 100~120V AC, 50/60Hz, 15A
Generator requirement	5000 Watt (disable idle-down feature)	5000 Watt (disable idle-down feature)	5000 Watt (disable idle-down feature)
<b>Features</b>			
Digi-Trac™	X		X
IntelliSync®	X	X	
ActivGuard™ GPS		X	
EZ-Tilt Cart		X	
<b>Included accessories</b>			
Spray gun	RX-Pro	RX-Pro	RX-Pro
Spray hose	50' (15 m) P/N 316-505	50' (15 m) P/N 316-505	50' (15 m) P/N 316-505
Spray filter	60 mesh, P/N 0089958	60 mesh, P/N 0089958	60 mesh, P/N 0089958
<b>Literature</b>			
Operation manual (Form No. 805-915)	English / French / Spanish included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>	English / French / Spanish included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>	English / French / Spanish included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>
Service manual (Form No. 2421887)	English / French / Spanish available online at <a href="http://www.titantool.com">www.titantool.com</a>	English / French / Spanish available online at <a href="http://www.titantool.com">www.titantool.com</a>	English / French / Spanish available online at <a href="http://www.titantool.com">www.titantool.com</a>
RX-Pro manual (Form No. 0538801)	All languages included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>	All languages included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>	All languages included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>
<b>Compliance</b>			
	Conforms to UL STD 1450 Certified to CSA STD C22.2 No. 68	Conforms to UL STD 1450 Certified to CSA STD C22.2 No. 68	Conforms to UL STD 1450 Certified to CSA STD C22.2 No. 68
Radio Frequency Approvals	<p>Transmitter Frequency (all models): 2.4GHz  Transmitter Power (all models): +8dBm  NOTE: FCC/IC Notice (all models)  Contains FCC ID: RYYEYSKBN  Contains IC: 4398B-EYSKBN</p> <p>The enclosed device complies with Part 15 of the FCC Rules and with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:(1) this device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.</p> <p>Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.</p> <p>This equipment is not granted protection against harmful interference and cannot cause interference on systems properly authorized.</p> <p>This equipment has the board BGM13P22A with homologation code ANATEL 01330-19-03402.</p>		