

HP	Type	FLA	RPM	V	PH	HP	Type	FLA	RPM	V	PH	HP	Type	FLA	RPM	V	PH
0.25	Open	5.1	1750	120	1	0.75	Open	11	1750	120	1	1.5	TEFC	16.4	1750	120	1
		2.1	1750	208	1			6.3	1750	208	1			9.5	1750	208	1
		2.3	1750	230	1			5.5	1750	240	1			8.2	1750	230	1
		1.1	1750	208	3			2.9	1750	208	3			4.3	1750	208	3
		1.4	1750	230	3			2.6	1750	240	3			4.4	1750	230	3
		0.75	1750	460	3			1.3	1750	460	3			2.2	1750	460	3
0.25	TEFC	3.6	1750	120	1	0.75	TEFC	11	1750	120	1	2	Open	20.4	1750	120	1
		2.2	1750	208	1			5.4	1750	208	1			10	1750	208	1
		1.9	1750	230	1			5.5	1750	230	1			10.2	1750	230	1
		1.6	1750	208	3			2	1750	208	3			7	1750	208	3
		1.4	1750	230	3			2.2	1750	230	3			6.6	1750	230	3
		0.7	1750	460	3			1.1	1750	460	3			3.5	1750	460	3
0.33	Open	5.5	1750	120	1	1	Open	0.8	1750	575	3	2	TEFC	24	1750	120	1
		3.2	1750	208	1			13	1750	120	1			12	1750	230	1
		2.8	1750	230	1			7.5	1750	208	1			6.5	1750	208	3
		1.4	1750	208	3			6.5	1750	240	1			5.8	1750	230	3
		1.6	1750	230	3			3.7	1750	208	3			2.9	1750	460	3
		0.8	1750	460	3			3.2	1750	240	3			2.3	1750	575	3
0.33	TEFC	4.6	1750	120	1	1	TEFC	1.6	1750	460	3	3	Open	14	3600	208	1
		2.3	1750	208	1			13	1750	120	1			12.4	3600	230	1
		2.4	1750	230	1			6.5	1750	230	1			9	3600	208	3
		1.2	1750	208	3			3.3	1750	208	3			8.6	3600	230	3
		1.2	1750	230	3			3.4	1750	230	3			4.3	3600	460	3
		0.6	1750	460	3			1.7	1750	460	3			3.6	3600	575	3
0.5	Open	8.8	1750	120	1	1.5	Open	1.4	1750	575	3	3	TEFC	30	3600	120	1
		5.1	1750	208	1			15	1750	120	1			15	3600	230	1
		4.4	1750	230	1			8.3	1750	208	1			8.5	3600	208	3
		3	1750	208	3			7.5	1750	230	1			8.2	3600	230	3
		2.5	1750	230	3			5.6	1750	208	3			4.1	3600	460	3
		1	1750	460	3			5	1750	230	3			3	3600	575	3
0.5	TEFC	7	1750	120	1	1.5	Open	2.7	1750	460	3	3	TEFC	15	3600	120	1
		3.4	1750	208	1			1.6	1750	575	3			8.5	3600	208	3
		3.5	1750	230	1									4.1	3600	460	3
		2.3	1750	208	3									3	3600	575	3
		2	1750	230	3												
		1	1750	460	3												
		0.7	1750	575	3												